

**Amendments to the Claims:**

This listing of the claims will replace all prior versions and listings of claims in the application:

**Listing of Claims:**

1 (Previously Presented): A battery pack malfunction detection apparatus that detects a malfunction in a battery pack constituted with a plurality of chargeable/dischargeable cells, comprising:

malfunction detection devices each provided in correspondence to a predetermined number of cells to detect an overcharge malfunction in the corresponding predetermined number of cells during an overcharge detection period and to detect an over-discharge malfunction in the corresponding predetermined number of cells during an over-discharge detection period;

a decision-making device that makes a decision as to whether or not a cell in an overcharge malfunction state or a cell in an over-discharge malfunction state exists based upon a signal input from each of the malfunction detection devices through a single signal line;

a clock signal generator; and

a switch, wherein:

each of the malfunction detection devices outputs a first signal if an overcharge malfunction is detected in any of the corresponding predetermined number of cells and outputs a second signal if no overcharge malfunction is detected during the overcharge detection period, outputs the second signal if an over-discharge malfunction is detected in any of the corresponding predetermined number of cells and outputs the first signal if no over-discharge malfunction is detected during the over-discharge detection period, and the clock signal generator controls the switch to repeatedly select the output signal to the single signal line during

the overcharge detection period and the output signal to the single signal line during the over-discharge detection period to the decision-making device.

2 (Original): A battery pack malfunction detection apparatus according to claim 1, wherein:

the decision-making device decides that there is a cell with an overcharge malfunction if the first signal is input from the malfunction detection device both during the overcharge detection period and during the over-discharge detection period.

3 (Original): A battery pack malfunction detection apparatus according to claim 1, wherein:

the decision-making device decides that there is a cell with an over-discharge malfunction if the second signal is input from the malfunction detection device both during the overcharge detection period and during the over-discharge detection period.

4 (Original): A battery pack malfunction detection apparatus according to claim 1, wherein:

each of the malfunction detection devices includes a voltage comparator that compares a terminal voltage at each of the corresponding predetermined number of cells with a reference voltage, outputs the first signal if the terminal voltage at any cell is higher than the reference voltage by using an overcharge decision-making voltage as the reference voltage during the overcharge detection period and outputs the second signal if the terminal voltage at any cell is lower than the reference voltage by using an over-discharge decision-making voltage as the reference voltage during the over-discharge detection period.

5 (Previously Presented): A battery pack malfunction detection apparatus according to claim 1, wherein:

each of the malfunction detection devices switches between an overcharge malfunction detection and an over-discharge malfunction detection based upon the clock signal generated by the clock generation device.

6 (Original): A battery pack malfunction detection apparatus according to claim 1, wherein:

the overcharge malfunction detection period and the over-discharge malfunction detection period extend over lengths of time different from each other.

7 (Original): A battery pack malfunction detection apparatus according to claim 1, wherein:

if a current consumed in the battery pack malfunction detection apparatus when the malfunction detection devices output a signal indicating that none of the corresponding predetermined number of cells is in an overcharged state is different from a current consumed in the battery pack malfunction detection apparatus when the malfunction detection devices output a signal indicating that none of the corresponding predetermined number of cells is in an over-discharged state, the signal requiring a larger current consumption is output over a smaller length of time than the signal requiring a smaller current consumption.

8 (Canceled)

9 (Canceled)

10 (Previously Presented): The battery pack malfunction detection apparatus according to claim 1, wherein the clock signal generator generates a clock signal which is input to each malfunction detection device and the switch.